

Product Information

- Dispensing contactless tickets
- Optional: Additional dispensing magnetic tickets (one track processing; ISO 2 or ISO 3 or ISO 9)
- Optional: Direct thermal printing on thermo-sensitive surfaces, graphic printing
- Reload function for tickets as well as PVC cards - only for electronic data carrier
- Integrated burster, easy to take off
- 2 feeding modules for Leporello tickets
- Functional LEDs
- Easy service by modular construction
- High reliability

Produktinformation

- Spenden von berührungslosen Tickets
- Optional: Zusätzlich Spenden von Magnet-Tickets (1-Spur-Verarbeitung; ISO 2 oder ISO 3 oder ISO 9)
- Optional: Direkter Thermodruck auf thermo-sensitiven Flächen, grafikfähig
- Aufladefunktion sowohl für berührungslose Tickets als auch für PVC-Karten
- Integrierte Reißereinheit, leicht abnehmbar
- Zwei Zuführungen für Leporello-Tickets
- Funktions-LEDs
- Einfacher Service durch modularen Aufbau
- Hohe Zuverlässigkeit

Information sur le produit

- Distribution de tickets sans contact
- En option: en outre distribution de tickets magnétiques (traitement d'une piste; ISO 2 ou ISO 3 ou ISO 9)
- En option: Impression thermique directe sur supports thermosensitifs, impressions graphiques
- Chargement de tickets sans contact ainsi que de cartes en PVC
- Rupteur intégré facilement démontable
- Double alimentation pour de tickets pliés en accordéon
- LEDs fonctionnels
- Maintenance aisée grâce à sa construction modulaire
- Haute fiabilité



POS TICKET DISPENSER


for contactless Tickets

POS TICKETSPENDER

für kontaktlose Tickets

DISTRIBUTEUR DE TICKETS

de tickets sans contact



CCS Challenge Card Systems GmbH
Rombacher Hütte 12a
44795 Bochum
Germany
☎ +49 (0)234 94391 - 0
☎ +49 (0)234 94391 - 99
info@ccs-cardtec.com
www.ccs-cardtec.com



Dimensions / Weight

W 200 mm H 700 mm D 500 mm / 19,8 kg

Power Supply

230 V AC / 50 Hz

Tickets

Thickness: 0.2 - 0.6 mm
Format: 54 x 85.6 mm
Material: paper, compound
Reload CSC up to 0.9 mm is possible
Bursting force: 4 - 7.5 daN

Ticket Transport Speed

Normal transport: 350 - 500 mm/s
Printing depending on paper quality: 50 - 100 mm/s

Print Head

Resolution: 8 dot/mm
Max. print width: 48 mm

Interface

USB 2.0
Communication protocol on request

User Interface

Functional LEDs
Luminated ON-OFF switch
BNC + Din-Connector for external antenna
ISO 14443 A/B

Microprocessor System

Firmware upgradable Microcontrollers
Service-Counter

Internal Ticket Dispenser

CCS 2960 KGB® with integrated CSC Antenna

Capacity for Ticket Stock

2 cartons with zig-zag folded paper tickets
with a ticket thickness of 0.4 mm

Reliability

MTBF*: > 20 000 h
MCBF*: > 200 000 tickets
MTTR: < 0.5 h in workshop

** without wear parts*

